



# ThyssenKrupp GfT Tiefbautechnik

<b>Antriebsaggregat</b> power pack <b>MS-A 660 (V)*</b>	<b>TA 0463</b>  Dat.: 16.01.2002 Name: K/U
---	---

TECHNISCHE DATEN:

Dieselmotor: Leistung  
 Drehzahl  
 Verteilergetriebe:  
 Dieseltank: max. vol.  
 Hydrauliktank: max. vol.  
 Gewicht: ohne Treibstoff

TECHNICAL DATA:

diesel engine: performance 656 [kW]  
 speed 2100 [min<sup>-1</sup>]  
 distributor gear 3 x i=0,73  
 fuel tank: max. volume 1200 [l]  
 hydraulic tank: max. vol. 210 [l]  
 weight: without fuel 9300 [kg]

PUMPENAUSRÜSTUNG:

Vibr.-Antriebspumpen:  
 Fördermenge: max.  
 Arbeitsdruck: max.  
 Spannhydr.-Pumpe:  
 Fördermenge:  
 Arbeitsdruck: max.  
 Steueröl-Pumpe:  
 Fördermenge:  
 Arbeitsdruck: max.  
 Kühler-Antriebspumpe:  
 (Vibratorgetriebe)  
 Fördermenge:  
 Arbeitsdruck: max.

PUMP EQUIPMENT:

vibr. drive pumps 130 [cm<sup>3</sup>/U]  
 delivery: max. 3 x 355 = 1065 [l/min]  
 working pressure: max. 380 [bar]  
 clamp-hydr. pump:  
 delivery: 10 [cm<sup>3</sup>/U]  
 21 [l/min]  
 working pressure: max. 350 [bar]  
 pump for amplitude:  
 delivery: 6 [cm<sup>3</sup>/U]  
 17 [l/min]  
 working pressure: max. 250 [bar]  
 cooler-drive pump:  
 (vibrator-gear) 11 [cm<sup>3</sup>/U]  
 delivery: 23 [l/min]  
 working pressure: max. 100 [bar]

KÜHLERAUSRÜSTUNG:

Dieselmotorkühler:  
 Lieferumfang Dieselmotor  
 Hydraulikölkühler:  
 Öl-Luft-Kühler  
 Kühlleistung:  
 Vibratorgetriebeöl-Kühler:  
 Öl-Luft-Kühler  
 Kühlleistung:

COOLER EQUIPMENT:

diesel engine cooler:  
 delivery volume diesel engine  
 hydr. oil cooler:  
 oil-air-radiator  
 cooling capacity: 96 [kW]  
 vibr. gear-oil cooler:  
 oil-air-radiator  
 cooling capacity: \*\* [kW]

\* = optional mit Amplitudenverstellung / optional with amplitude adjustment  
 \*\* = abhängig von Vibrator / dependent on vibrator

Subject to Technical modifications

Distributed in Australia & New Zealand by <b>ThyssenKrupp Steelcom</b> <small>A company of ThyssenKrupp Services</small>		
PO Box 840 North Sydney NSW 2059 Australia T: + 61 2 9954 9166 Sales + 61 2 4966 0688 F: + 61 2 9955 4298 enquiries@steelcom.com.au www.steelcom.com.au	PO Box 51254 Pakuranga Auckland 2140 New Zealand T: + 64 9 576 3977 F: + 64 9 576 3978 afenn@steelcomnz.co.nz www.steelcomnz.co.nz	